



# PHASED OUT UNITS

**SPECIAL PRICING**

## DNF400/410

**Energy Saving**

Forced Convection Ovens with Variable Flow Rate



**Special price \$3,250**

- Operation mode: Fixed temperature, Program operation, Auto start, Auto stop
- Safety device: Self diagnosis functions (temp. sensor abnormal, Heater disconnection, SSR-short, Main relay abnormal, Automatic overheating prevention), Key lock function, Independent overheat prevention, Electric leakage breaker with over current protection

Model	DNF400	DNF410
Method	Air velocity control, Forced air circulation (with manual slide to operate the exhaust damper)	
Temperature range	RT +10 to 260°C	
Temperature control accuracy	±0.5°C (at 260°C)	
Temperature distribution accuracy	±2.5°C (max. air velocity, at 260°C)	
Capacity	90L	
Power source	AC115V 11.5A	AC220V 6A

## DF410C

High-performance Fine Oven



**Special price \$3,100**

- Operation mode: Fixed temperature, Quick auto stop, Auto stop, Auto start, Program operation
- Safety device: Circuit breaker, Overheating prevention device
- Self-diagnostic functions: failure of sensor, heater, SSR, memory, internal communication, temperature inputting circuit, automatic overheating prevention device, overheating prevention device, measurement temperature

Method	Forced circulation
Temperature range	RT +10 to 260°C
Temperature control accuracy	±0.1°C at 260°C
Temperature distribution accuracy	±1.5°C at 260°C
Capacity	91L
Power source	220V single phase, 10A

## DH410C

High-performance Fine Oven



**Special price \$3,000**

- Operation mode: Fixed temperature, Quick auto stop, Auto stop, Auto start, Program operation
- Safety device: Circuit breaker, Overheating prevention device
- Self-diagnostic functions: failure of sensor, heater, SSR, memory, internal communication, temperature inputting circuit, automatic overheating prevention device, overheating prevention device, measurement temperature

Method	Forced circulation
Temperature range	RT +10 to 360°C
Temperature control accuracy	±2°C at 360°C
Temperature distribution accuracy	±2.5°C at 360°C
Capacity	91L
Power source	220V single phase, 13A

## SM200

Standard Laboratory Use Sterilizer with Dryer



**Special price \$4,200**

- Safety device: Self-diagnostic functions (detection sensor error, SSR short circuit, heater disconnect, faulty main relay, dry operation), safety valve, electric leakage breaker, drain bottle set-fail switch
- Accessories: 2 pcs. stainless steel mesh basket (Dia.205 x D204mm), OSM-60, drain board x 1, chemical indicator strips (30 strips) x 1, drain bottle x 1, condensation collection container with magnetic bracket x 1

System	Automatic high pressure steam sterilizer	
Temperature range	Sterilization	105°C~123°C
	Drying	150°C~180°C
Maximum operational pressure	0.18MPa (26.1psi)	
Capacity	20L	
Power source	AC115V 13A (50/60Hz)	

## PDC210

Gas Plasma Dry Cleaner



**Special price \$28,000**

- Simple and compact plasma surface treatment device
- RIE (Reactive Ion Etching) Plasma mode, with DP (Direct Plasma) mode as option
- Excellent electrode structure for plasma uniformity
- Simple touch panel system

Plasma mode	RIE (DP mode option)
Chamber size	W400 × D250 × H150mm
Power source	Single phase AC220V 50/60Hz

### Yamato Scientific America Inc.

Toll free: 1-800-292-6286  
 Tel: 1-408-235-7725 / Fax: 1-408-235-7730  
 customerservice@yamato-usa.com  
 www.yamato-usa.com