

SINCE 1889



PHASED OUT UNITS

SPECIAL PRICING

DNF400/410

Energy Saving

Forced Convection Ovens with Variable Flow Rate



Special price
\$3,250

- Operation mode: Fixed temperature, Program operation, Auto start, Auto stop
- Safety device: Self diagnosis functions (temp. sensor abnormal, Heater disconnection, SSR-short, Main relay abnormal, Automatic overheating prevention), Key lock function, Independent overheat prevention, Electric leakage breaker with over current protection

Model	DNF400	DNF410
Method	Air velocity control, Forced air circulation (with manual slide to operate the exhaust damper)	
Temperature range	RT +10 to 260°C	
Temperature control accuracy	±0.5°C (at 260°C)	
Temperature distribution accuracy	±2.5°C (max. air velocity, at 260°C)	
Capacity	90L	
Power source	AC115V 11.5A	AC220V 6A

DF410C

High-performance Fine Oven



Special price
\$3,100

- Operation mode: Fixed temperature, Quick auto stop, Auto stop, Auto start, Program operation
- Safety device: Circuit breaker, Overheating prevention device
- Self-diagnostic functions: failure of sensor, heater, SSR, memory, internal communication, temperature inputting circuit, automatic overheating prevention device, overheating prevention device, measurement temperature

Method	Forced circulation
Temperature range	RT +10 to 260°C
Temperature control accuracy	±0.1°C at 260°C
Temperature distribution accuracy	±1.5°C at 260°C
Capacity	91L
Power source	220V single phase, 10A

DH410C

High-performance Fine Oven



Special price
\$3,000

- Operation mode: Fixed temperature, Quick auto stop, Auto stop, Auto start, Program operation
- Safety device: Circuit breaker, Overheating prevention device
- Self-diagnostic functions: failure of sensor, heater, SSR, memory, internal communication, temperature inputting circuit, automatic overheating prevention device, overheating prevention device, measurement temperature

Method	Forced circulation
Temperature range	RT +10 to 360°C
Temperature control accuracy	±2°C at 360°C
Temperature distribution accuracy	±2.5°C at 360°C
Capacity	91L
Power source	220V single phase, 13A

PDC210

Gas Plasma Dry Cleaner



Special price
\$28,000

- Simple and compact plasma surface treatment device
- RIE (Reactive Ion Etching) Plasma mode, with DP (Direct Plasma) mode as option
- Excellent electrode structure for plasma uniformity
- Simple touch panel system

Plasma mode	RIE (DP mode option)
Chamber size	W400 × D250 × H150mm
Power source	Single phase AC220V 50/60Hz

Yamato Scientific America Inc.

Toll free: 1-800-292-6286
Tel: 1-408-235-7725 / Fax: 1-408-235-7730
customerservice@yamato-usa.com
www.yamato-usa.com