









OVEN OVERVIEW

	Series	Model No.	Operating Temperature Range					Internal Capacity (L)	Program	Characteristics
			0	100	200	300	400			
Natural Convection	DX	302C/312C	RT+5~300°C					28	--	<ul style="list-style-type: none"> Economical High temperature Do not use fans. Heat rises by natural air convection for a slower heat flow 
		402C/412C						74	--	
		602C/612C	RT+5~280°C					153	--	
	DVS	402C/412C	RT+5~260°C					99	Yes	
		602C/612C						162	Yes	
	DR	200	300~700°C					13.75	Yes	
	DG	400C/410C						92	--	
		440C/450C						92	--	
		800C/810C	RT+5~70°C					445	--	
840C/850C*							445	--		
Forced Convection	DKM	300C/310C						27	--	<ul style="list-style-type: none"> High level of air circulation, accuracy and uniformity Use fan motors for vertical air circulation providing a more uniform heat flow Built-in exhaust port Calibration offset function 
		400C/410C	RT+10~260°C					90	--	
		600C/610C						150	--	
	DKN	302C/312C						27	Yes	
		402C/412C	RT+10~260°C					90	Yes	
		602C/612C						150	Yes	
		812C						300	Yes	
	DNE	912C	RT+10~210°C					535	Yes	
		401/411	RT+20~210°C					90	Yes	
		601/611						150	Yes	
	DNF	811	RT+15~210°C					300	Yes	
		911						540	Yes	
		301						27	Yes	
		401/411	RT+15~260°C (Wind velocity: 1~10)					90	Yes	
		601/611						150	Yes	
Fine	DF	412	RT+15~260°C					91	Yes	<ul style="list-style-type: none"> Rapid & high volume of airflow Use forced convection for a horizontal air flow as opposed to vertical Very high uniformity, accuracy and performance Quick exhaust and cooling 
		612						216	Yes	
		832	RT+15~200°C					512	Yes	
		1032						1000	Yes	
DH	412	RT+15~360°C					91	Yes		
	612						216	Yes		
	832	RT+15~300°C					512	Yes		
	1032						1000	Yes		
Vacuum	ADP	200C/210C	40~240°C					10	Yes	<ul style="list-style-type: none"> Handle sensitive samples at lower temperature Heat is evenly distributed from arrangement of the heaters against outer chamber walls Reduced oxidation 
		300C/310C						27	Yes	
	DP	43C						91	Yes	
		63C	40~200°C					512L	Yes	
		103C						216	Yes	
Clean Inert	DN	411IE	RT+15~360°C					95	Yes	<ul style="list-style-type: none"> Creates non-oxidative environment Controllable nitrogen flow 
		611IE						223	Yes	
Clean	DES	830	RT+30~260°C					327	Yes	<ul style="list-style-type: none"> Class 100 Stable cleanliness through forced circulation with rear exhaust 
	DTS	830	RT+30~360°C					327	Yes	